Applicant(s): P. Bonutti Application No.: 10/685,117

Examiner: K. Truong

Amendments to the Claims

1-3. (canceled)

4. (Currently amended) A bone suture assembly for treating a fracture of a bone

comprising:

a first rigid bone plate positionable proximate to the bone;

a second rigid bone plate positionable proximate to the bone generally opposite the first

bone plate;

a suture connected with the first and second rigid bone plates to thereby stabilize the

fracture, the suture positionable through a passage in the bone; and

at least one fastener positionable through the first rigid bone plate into the bone to hold

the first rigid bone plate to the bone.

5-7. (canceled)

8. (Currently amended) A bone suture assembly for treating a fracture of a bone

comprising:

a first bone plate positionable proximate to the bone;

a suture positionable through the first bone plate and across the fracture of the bone to

thereby stabilize the fracture; and

a tubular member positionable in the bone through the fractured bone, generally

orthogonal to the first bone plate, wherein the tubular member remains in the bone such that the

suture is disposed within the tubular member.

9. (original) A bone suture assembly as defined in claim 8 wherein the tubular member is

packed with bone particles.

10. (original) A bone suture assembly as defined in claim 8 wherein the tubular member is

packed with bone osteoinductive protein.

2

Applicant(s): P. Bonutti Application No.: 10/685,117

Examiner: K. Truong

11. (previously presented) A bone suture assembly as defined in claim 4 wherein the passage

is nonlinear.

12. (original) A bone suture assembly as defined in claim 11 wherein at least one tubular

member is disposed within the nonlinear passage and wherein the suture is disposed within at

least one tubular member.

13. (Currently amended) A bone suture assembly for treating a fracture of a bone

comprising:

a first suture anchor positionable proximate to the bone;

a rigid bone plate positionable between the first suture anchor and the bone, the rigid

bone plate and first suture anchor positionable generally on the same side of the bone; and

a suture extending through the rigid bone plate and connected with the first suture anchor,

the suture positionable across the bone to thereby stabilize the fracture; and

at least one fastener positionable through the rigid bone plate into the bone to hold the

rigid bone plate to the bone.

14. (previously presented) A bone suture assembly as defined in claim 13 further including a

second suture anchor positionable at a location spaced from the first suture anchor, the second

suture anchor connected with the suture.

15. (canceled)

16. (previously presented) A bone suture assembly as defined in claim 14 further including a

passage through bone located between the first and second suture anchors, wherein the suture is

disposed within the passage.

17. (Canceled)

3

Applicant(s): P. Bonutti Application No.: 10/685,117

Examiner: K. Truong

18. (Currently amended) A bone suture assembly as defined in claim 17 14 wherein at least one fastener extends across the fracture of the bone.

- 19. (canceled)
- 20. (Currently amended) A bone suture assembly as defined in claim 47 14 wherein the at least one fastener includes a screw.
- 21. (original) A bone suture assembly as defined in claim 14 wherein the first and second suture anchors are suture retainers.
- 22. (original) A bone suture assembly as defined in claim 21 wherein the suture retainers include deformable material to hold the suture retainers to the suture.
- 23. (Currently amended) A method for treating a fracture of a bone comprising:

 forming at least one passage through the bone, where the passage traverses the fracture;

 positioning at least one suture anchor proximate to the bone;

 positioning at least one bone plate between at least one suture anchor and the bone;

 fastening the at least one bone plate to the bone with at least one screw;

 moving at least one suture across the fracture of through the passage in the bone and through at least one bone plate;

attaching at least one suture to at least one suture anchor; and tensioning at least one suture to stabilize the fracture of the bone.

- 24. (original) A method as defined in claim 23 wherein at least one suture anchor is a suture retainer.
- 25. (Canceled)
- 26. (Currently amended) A method as defined in claim 25 23 wherein at least one screw has

Applicant(s): P. Bonutti Application No.: 10/685,117

Examiner: K. Truong

a length less than a diameter of the bone.

27. (Currently amended) A method as defined in claim 25 23 wherein at least one screw has

a length greater than a diameter of the bone.

28. (original) A method as defined in claim 27 wherein at least one screw includes at least

one nut.

29. (original) A method as defined in claim 28 wherein at least one screw extends across the

fracture of the bone.

30. (Canceled)

31. (Currently amended) A method as defined in claim 30 23 wherein attaching at least one

suture to at least one suture anchor is performed prior to moving at least one suture, and wherein

moving at least one suture includes moving at least one suture attached to at least one suture

anchor through at least one passage.

32. (original) A method as defined in claim 31 further including changing the orientation of

at least one suture anchor from a first to a second configuration thereby causing at least one

suture anchor to become proximate to the bone and impassable through at least one passage.

33. (original) A method as defined in claim 32 wherein tensioning at least one suture

includes tensioning at least one suture between at least two suture anchors to stabilize the

fracture of the bone.

34. (previously presented) A bone suture assembly as defined in claim 14 wherein the suture

includes a plurality of generally parallel suture sections.

35. (previously presented) A bone suture assembly as defined in claim 34 further including a

5

Applicant(s): P. Bonutti Application No.: 10/685,117

Examiner: K. Truong

passage through bone located between the first and second suture anchors, wherein the plurality of generally parallel suture sections is disposed within the passage.

- 36. (previously presented) A bone suture assembly as defined in claim 4 wherein the suture is positionable through the fracture.
- 37. (previously presented) A bone suture assembly as defined in claim 4 wherein at least one of the bone plates includes a channel extending between a bone-contacting surface of the plate and a non-bone-contacting surface of the plate, and wherein the suture is positioned in the channel.
- 38. (previously presented) A bone suture assembly as defined in claim 37 wherein the surfaces face in generally opposite directions.